

Autoscope® Pn-500



The Autoscope Pn-500 video detection system provides a complete solution for junction control. The Pn-500 detector card slides easily into a rack to provide stopline and approach vehicle detection at each approach.

The smartly designed and compact Sn-500 camera delivers value in a compact package to view traffic at the junction.

With its enhanced features, both video inputs are now processed at full frame rate for improved performance in detection of faster moving vehicles.

The detector card contains 16 open collector outputs, each with status LEDs on the front panel as well as mini-USB for setup.

Traffic managers will benefit from this streamlined and cost-effective solution that offers non-intrusive fast setup, minimal maintenance, and high performance.

BENEFITS

- Cost-effective solution for junction control
- Field proven accuracy and reliability through ISS Terra technology
- Easy to install, configure and maintain
- Easily integrated into controllers and detector racks

FEATURES

- Vehicle presence detection
- Dual-camera video processor
- Enhanced USB or TCP/IP connectivity (through adapter)
- 64-pin DIN connector backplane provides convenient terminations for power, communications, detector I/O and video inputs
- Vehicle presence outputs via backplane screw terminations
- Provides bicycle detection on all detectors, differentiation on all approaching lanes, at any point in the field of view
- LED indicates status for power, communications, video, and detector I/O
- Low power consumption

APPLICATIONS

- Junction control
- Ramp monitoring
- Advance detection



Autoscope Pn-500

SPECIFICATION

Processor

Power

- 12 to 24 VDC, 8W maximum)

Video

Input

- PAL (25 fps), NTSC (30 fps)
- Two Channels 75Ω 1 Vpp, BNC connector

OR

- Screw terminal differential video connections

Output

- 1 Vpp, BNC connector on front
- PAL or NTSC

Communications

- USB Supervisor communication via mini-USB connector on front
- Ethernet communication via USB to Ethernet adapter (optional).

Detector I/O

- 16 outputs, (open collector, selectable active low or high by hardware jumper)
- 4 inputs
- 1 status output (open collector, active low) to indicate card is processing and detector I/O valid

Camera

- Compatible with the Autoscope Sn-500 CAM CMOS sensor or with the Autoscope Pn-500 CCD sensor

Environmental

- -34° C to +74° C (-29° F to +165° F)
- 0 to 95% relative humidity, non-condensing

Dimensions and Weight

- H x W x L (3U x 160mm)
130 mm x 20 mm x 207 mm
(5.12 in x 0.80 in x 8.15 in)
- 0.16 kg (0.35 lb)

Warranty

- Two-year warranty
- Extended warranty package available

Regulatory

- CE EN 55024, EN 55032, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, RoHS

SET-UP AND OPERATION

The Autoscope Pn-500 system is easy to install, set up, and operate to meet your vehicle detection requirements.

- Processor slides directly into detector racks.
- Setup uses simple mouse and keyboard commands via the Autoscope software to create detection zones for up to 4 lanes per camera for vehicle presence applications.

CONTACTS

World Headquarters

500 Spruce Tree Centre
1600 University Avenue West
St. Paul, MN 55104 USA
Phone: +1.651.603.7700
Fax: +1.651.305.6402
info@imagesensing.com
imagesensing.com

Image Sensing Systems Romania

Dobrogeanu Gherea Constantin Street
10-12, et1, ap1
Sector 1, 013764, Bucharest
Romania
Phone +4.021.794.55.60
Fax +4.021.794.55.66
issro@imagesensing.com

Image Sensing Systems Spain

C/ Consell de Cent 357-359, 5-1
08087 Barcelona
Spain
sales@imagesensing.com

