

# Autoscope® Sn-510



The Autoscope Sn-510 video detection system provides a complete solution for junction control. The Sn-510 DIN rail processing card easily integrates into traffic cabinets to provide stopline and approach vehicle detection for up to four approaches.

The smartly designed camera delivers value in a compact package to view traffic at the junction.

With its new simple detection zone setup tool, the Sn-510 can be setup in less than 15 minutes.

The detector card contains 16 open collector outputs, each with status LEDs on the front panel as well as micro-USB for setup.

Traffic managers will benefit from this streamlined and cost-effective solution that offers non-intrusive fast setup, minimal maintenance and high performance.

## APPLICATIONS

- Junction control
- Advance detection

## FEATURES

- Vehicle presence detection
- Four-camera video processor
- Enhanced USB or TCP/IP connectivity (through adapter)
- Front panel provides convenient terminations for power, communications, detector I/O and video inputs
- 6 securable, plug-style connectors with screw terminals that plug easily into the unit
- Vehicle presence outputs via front panel screw terminations
- LED indicates status for power, communications, video and detector I/O
- Low power consumption

## BENEFITS

- Cost-effective solution for junction control
- Field proven accuracy and reliability
- Easy to install, configure and maintain
- Easily integrated into controllers and detector racks



# Autoscope Sn-510

## SPECIFICATION

### Processor

#### Power

- 12 to 28 VDC, 8W maximum

#### Video

#### Input

- PAL (25 fps), NTSC (30 fps)
- Four Channels 100Ω 1 Vpp, plugable screw terminal block differential video connections

#### Output

- Digital stream

#### Communications

- Supervisor communication via micro USB connector on front
- Ethernet communication via USB to Ethernet adapter (optional).

#### Detector I/O

- 16 outputs, (open collector, selectable active low or high by hardware jumper)
- 4 inputs
- 1 status output (open collector, active low) to indicate card is processing and detector I/O valid

#### Environmental

- -34° C to +74° C (-29° F to +165° F)
- 0 to 95% relative humidity, non-condensing

#### Dimensions and Weight

- H x W x L  
135 mm x 55 mm x 170 mm  
(5.31 in x 2.71 in x 6.69 in)
- 0.27 kg (0.6 lb)

#### Warranty

- Two-year warranty
- Extended warranty package available

#### Regulatory

- CE EN 55022, EN55024, EN 61000-6-1, RoHS

## SET-UP AND OPERATION

The Autoscope Sn-510 system is easy to install, set up, and operate to meet your vehicle detection requirements.

- DIN rail processing card easily integrates into traffic cabinets.
- Setup uses a new simple detection zone setup application to create detection zones for up to 4 approaches and allows a user to have a system up and running within minutes. The Autoscope software to create detection zones for up to 4 lanes per camera for vehicle presence applications.

## CONTACTS

### World Headquarters

500 Spruce Tree Centre  
1600 University Avenue West  
St. Paul, MN 55104 USA  
Phone: +1.651.603.7700  
Fax: +1.651.305.6402  
info@imagesensing.com  
imagesensing.com

### Image Sensing Systems Romania

Dobrogeanu Ghenea Constantin Street  
10-12, et1, ap1  
Sector 1, 013764, Bucharest  
Romania  
Phone +4.021.794.55.60  
Fax +4.021.794.55.66  
issro@imagesensing.com

### Image Sensing Systems Spain

C/ Consell de Cent 357-359, 5-1  
08087 Barcelona  
Spain  
sales@imagesensing.com

